

Product Data Sheet

HP12 BASE COAT

HP12 Base uses 'High Polymer' technology for a cost effective enhanced performance on difficult substrates. It is ideal as a stipple coat or for dense backgrounds and has increased water resistance and adhesion. Incorporation of Alkali Resistant Reinforcing Mesh may be required.

K Rend base coats are polymer modified and cement based to ensure flexibility and strength. Scratch coats require only the addition of water and 5 minutes mixing time. Normally applied in 1 coat as a backing for K Rend finishes. Rule off to a flat finish and scratch lightly to provide a key for the next coat.

HP12 Base can be used in some instances as part of a waterproofing system. It has been used as a backing coat for swimming pools, and in house tests show excellent resistance to chlorinated water. Specialist technical advice must always be sought prior to use in this type of application. Due to its outstanding adhesion K Rend HP12 Base Coat also makes an excellent scud coat.

Coverage:

1.8kg / mm thick / sq m



Require:

6-9kg / sq m approx
nominal 4-6mm thickness

Support Backings

- HP12 Base can be used over block work masonry or stone backgrounds
- For insulation concrete refurbishment work or any other unusual substrate seek technical advice

Application

- Mix for at least 5 minutes to break down additives
- Add 4-5 litres of clean water per 25kg sack
- Apply by hawk and trowel
- If the next coat is to be a K Rend finish form a light key by scratching as per good render practice
- Alternatively float to a flat finish

Kitemark Classifications

Compressive strength: CS III

Capillary Water Absorption Category: W2

Thermal Conductivity: P = 50% - 0.35 & P = 90% - 0.40

In line with our policy of continuous product development, we reserve the right to change technical data without notice.



Kilwaughter Chemical Co Ltd

For UK Sales
9 Starbog Rd, Larne, Co. Antrim, N. Ireland, BT40 2TJ
Tel: 028 2826 0766 Fax: 028 2826 0136
Email: Sales@Kilwaughter.com
www.K-Rend.co.uk

Irish Aggregates Ltd

For ROI Sales
Classis, Ovens, Co. Cork, Ireland
Tel: 021 4872733 Fax: 021 4871705
Email: info@IrishAggregates.ie
www.IrishAggregates.com