

K DASH

TRADITIONAL FINE MORTAR

BUTTER COAT FOR DRY DASH APPLICATIONS
MAY BE HAND OR SPRAY APPLIED
SUITABLE FOR USE AS A DASH RECEIVER
APPLIED ONTO AN APPROPRIATE BASECOAT

K Dash Traditional Fine Mortar is manufactured to ISO 9001 and provides a cost-effective solution for dry dashing.

For general use, normally applied on to an approved basecoat. Apply 6 - 8mm thick, depending on the size of the dashing aggregate.

Coverage: 1.8kg per mm thick per sq m. Required: 10-18kg per sq m approx.

APPLICATION

Add 4 - 5 litres of clean water per 25kg sack

Mix thoroughly for at least 5 minutes

Apply a butter coat of render to a uniform thickness, depending on the aggregate size. While the render is still plastic, throw washed aggregate onto the surface to give a uniform dense coverage.

Immediately tamp the aggregate particles lightly into the butter coat with a wood float and ensure a good bond is obtained.

SITE CONDITIONS

Use only in temperature range 5°C to 35°C

Protect the working area before and after application

HEALTH AND SAFETY

Cement powder mixed with water releases alkali.

It is also important not to kneel or sit on wet material as harmful contact can occur through saturated clothing.

Keep out of reach of children.

Use barrier cream if necessary. Eye protection is recommended.

Direct skin contact should be avoided.

TECHNICAL ADVICE

A technical advisory service is available on request



Certificate No. FM65394



Certificate No. 06/0248



Kilwaughter Chemical Co Ltd

For UK Sales

9 Starbog Rd, Larne, Co. Antrim, N. Ireland, BT40 2TJ

Tel: 028 2826 0766 Fax: 028 2826 0136

Email: Sales@Kilwaughter.com

www.K-Rend.co.uk

Irish Aggregates Ltd

For ROI Sales

Classis, Ovens, Co. Cork, Ireland

Tel: 021 4872733 Fax: 021 4871705

Email: info@IrishAggregates.ie

www.IrishAggregates.com