

Product Data Sheet

K REND R10

K Rend R10 is a modified acrylic bonding coat designed to improve the adhesion of K Rend renders to difficult substrates, where the background does not provide sufficient key or as poor suction characteristics. If applied according to the manufacturer's instructions it can improve a difficult substrate and prepare the background for application of K Rend one coat renders.

- K Rend R10 is a low odour, ready to use primer which is quick and easy to apply by roller or brush
- K Rend R10 is self-coloured, to indicate areas treated for ease of use
- K Rend R10 allows the application of one-coat renders onto difficult substrates such as site cast concrete or higher suction block
- Apply K Rend R10 by roller or brush and allow to dry before applying top coat
- Drying times may be prolonged by lower temperatures and/or high humidity
- High suction backgrounds (i.e. lightweight concrete) may require two coats

Product Information

Appearance: Self-coloured paste

Density: Approximately 1.2kg/m³

Coverage: Approximately 0.25 to 0.45kg/m², depending on substrate and application technique. Higher suction backgrounds require more material and may require two coats.

Preparation

- For use on masonry substrates with "difficult" suction properties i.e. dense and lightweight concrete and clay brick
- Backgrounds should be clean, level, dry and free from efflorescence and loose, friable materials
- Mask all adjacent surfaces including window sills, doors, timber, glass, brick and flooring
- Protect weather exposed surfaces

Application

- The temperature of the substrate and surrounding air should be a minimum of 5°C
- Do not apply in conditions of strong sunshine or wind; do not apply onto damp or frozen substrates
- Stir bucket contents thoroughly before use; do not add water to product

Cleaning

Clean tools and equipment with water immediately after use. If the product has been left to harden it can only be removed mechanically.

Packaging

- 20kg plastic tubs
- The shelf life is approximately one year if stored off ground in original, sealed containers and protected against frost and away from direct sunlight

Other Information

Safety: The product is non hazardous if used according to the manufacturer's instructions; a separate material safety data sheet is available on request.

A Technical advisory service is available on request.

Product Data Sheet (contd.)

GUARANTEE & TECHNICAL ADVICE

A technical advisory service is available on request.

All Specifications are developed and owned by Kilwaughter Chemical Co Ltd for use as internal / external wall coverings. Kilwaughter Chemical Co Ltd use the Specifications in conjunction with its other standard form documents and technical data sheets and in compliance with professional bodies such as RIBA. Kilwaughter Chemical Co Ltd does not use the Specifications for any other purpose and does not consider them suitable for use for any other purpose. Electronic copies of specifications in MS Word format are not to be supplied outside the company. Kilwaughter Chemical Co Ltd does not permit the possession or use of electronic copies of specifications or guides to specifications by non Kilwaughter Chemical Co Ltd organisations or persons other than as stated above.

In line with our policy of continuous product development, we reserve the right to change technical data without notice.



Certificate No.
FM85394



BSEN998-1 & BSEN998-2
Licence No. 514639



Certificate No: 06/0248



Kilwaughter Chemical Co Ltd

For UK Sales

9 Starbog Rd, Larne, Co. Antrim, N. Ireland, BT40 2TJ
Tel: 028 2826 0766 Fax: 028 2826 0136
Email: Sales@K-Rend.co.uk
www.K-Rend.co.uk

For ROI Sales

Classis, Ovens, Co. Cork, Ireland
Tel: 021 4872733 Fax: 021 4871705
Email: Sales@K-Rend.co.uk
www.K-Rend.co.uk