

Product Data Sheet

K Pro

K Pro is a water based protective treatment used to provide long term, enhanced water repellent properties to external render and other masonry surfaces.

K Pro helps combat the problems associated with water intrusion including efflorescence, frost, water-soluble pollutants and algae growth.

K Pro provides increased resistance to oil absorption, enabling the substrate to stay clean and dry for longer allowing the background to breathe, maintaining the water vapour permeability of the substrate.

Substrates

K Pro can be used to treat a wide variety of substrates including:

- Cement based external render
- Brickwork & facades
- Sand lime bricks
- Natural & artificial stone
- Porous concrete

Appearance

- Form: milky/opaque, free flowing liquid (clear when fully dry)
- Density: 1.0 (approximately)
- pH: 7 (approximately)

Preparation

- It is recommended that a trial on an inconspicuous area is first carried out to ensure suitability of the product and final appearance of the treated surface
- The surface to be treated should be clean and free from any loose or friable material, including algae
- For best results apply onto a dry background
- For optimum effectiveness substrate must be totally dry to allow deep penetration
- Mask all adjacent surfaces including windows, sills, doors, timber, glass, brick and flooring

Application

- Stir or shake before use
- Can be applied by roller, painting, flooding or airless spraying
- Application rate: approximately 5 sq. metres per litre per coat, depending on the absorbency of the surface to be treated
- For optimum protection a second coat should be applied
- Initial water and oil resistance develops within 24 hours of application and improves with time

Cleaning

- Rinse tools and equipment with water

Packaging

- K Pro is packed in 25 Litre screw cap plastic containers
- The shelf life is approximately 6 months if stored off ground in original, sealed containers and protected against frost and away from direct sunlight


Safety

- K Pro is non flammable
- Please refer to the separate Material Safety Data Sheet

Technical Advice

- A technical advisory service is available on request
- In line with our policy of continuous product development, we reserve the right to change technical data without notice

In line with our policy of continuous product development, we reserve the right to change technical data without notice.



Kilwaughter Minerals Ltd

For UK Sales

9 Starbog Rd, Larne, Co. Antrim, N. Ireland, BT40 2TJ

Tel: 028 2826 0766 Fax: 028 2826 0136

Email: Sales@K-Rend.co.uk

www.K-Rend.co.uk

For ROI Sales

Classis, Ovens, Co. Cork, Ireland

Tel: 021 4872733 Fax: 021 4871705

Email: Sales@K-Rend.co.uk

www.K-Rend.co.uk