

Product Data Sheet

K Pro

K Pro is a water based protective treatment used to provide long term, enhanced water repellent properties to external render and other masonry surfaces.

K Pro helps combat the problems associated with water intrusion including efflorescence, frost, water-soluble pollutants and algae growth.

K Pro provides increased resistance to oil absorption, enabling the substrate to stay clean and dry for longer allowing the background to breathe, maintaining the water vapour permeability of the substrate.

Substrates

K Pro can be used to treat a wide variety of substrates including:

- Cement based external render
- Brickwork & facades
- Sand lime bricks
- Natural & artificial stone
- Porous concrete

Appearance

- Form: milky/opaque, free flowing liquid (clear when fully dry)
- Density: 1.0 (approximately)
- pH: 7 (approximately)

Preparation

- It is recommended that a trial on an inconspicuous area is first carried out to ensure suitability of the product and final appearance of the treated surface
- The surface to be treated should be clean and free from any loose or friable material, including algae
- For best results apply onto a dry background
- Mask all adjacent surfaces including windows, sills, doors, timber, glass, brick and flooring

Application

- Stir or shake before use
- Can be applied by roller, painting, flooding or airless spraying
- Application rate: approximately 5 sq. metres per litre per coat, depending on the absorbency of the surface to be treated
- For optimum protection a second coat should be applied as soon as the first coat has soaked in and before it fully dries
- Initial water and oil resistance develops within 24 hours of application and improves with time

Cleaning

- Rinse tools and equipment with water

Packaging

- K Pro is packed in 25 Litre screw cap plastic containers
- The shelf life is approximately 6 months if stored off ground in original, sealed containers and protected against frost and away from direct sunlight


Safety

- K Pro is non flammable
- Please refer to the separate Material Safety Data Sheet

Technical Advice

- A technical advisory service is available on request
- In line with our policy of continuous product development, we reserve the right to change technical data without notice

All Specifications are developed and owned by Kilwaughter Minerals Ltd for use as internal / external wall coverings. Kilwaughter Minerals Ltd use the Specifications in conjunction with its other standard form documents and technical data sheets and in compliance with professional bodies such as RIBA. Kilwaughter Minerals Ltd does not use the Specifications for any other purpose and does not consider them suitable for use for any other purpose. Electronic copies of specifications in MS Word format are not to be supplied outside the company. Kilwaughter Minerals Ltd does not permit the possession or use of electronic copies of specifications or guides to specifications by non Kilwaughter Minerals Ltd organisations or persons other than as stated above. In line with our policy of continuous product development, we reserve the right to change technical data without notice.



Kilwaughter Minerals Ltd

For UK Sales

9 Starbog Rd, Larne, Co. Antrim, N. Ireland, BT40 2TJ
Tel: 028 2826 0766 Fax: 028 2826 0136

Email: Sales@K-Rend.co.uk
www.K-Rend.co.uk

For ROI Sales

Classis, Ovens, Co. Cork, Ireland
Tel: 021 4872733 Fax: 021 4871705

Email: Sales@K-Rend.co.uk
www.K-Rend.co.uk