

Introducing Mineral TC

New **Mineral TC** is an easy to use, reliable cement based, polymer modified, self-coloured mineral thin coat render.

- ✓ Faster drying times at lower temperatures and high humidity
- ✓ Available in 2 textures (**Mineral TC 2 & Mineral TC 4**) and 4 standard colours
- ✓ Primarily for external render, can be used internally
- ✓ Requires only the addition of water and 10 minutes mixing time



Scan for info



Pure White



Granite



Pearl



Wheaten

Application

- Apply fresh basecoat a minimum of 14 days before work commences
- Prime walls using K Rend Primer TC, colour co-ordinated to topcoat and allow 24 hours to dry before applying topcoat
- Add 5 - 6 litres of water per 25kg sack
- Mix thoroughly for 10 minutes
- Apply the product to the thickness of the largest grain size using a stainless steel float and allow to take up slightly
- Rub the surface in circular motions using a plastic float to create texture

Preparation

- A test panel to check colour and final appearance is recommended
- It is recommended that a K Rend basecoat is applied as a background for K Rend Mineral TC
- Backgrounds should be clean, level, dry and free from efflorescence
- Mask all adjacent surfaces including windows, sills, doors, timber, glass, brick & flooring
- Protect weather exposed surfaces

Colour

- Available in two textures and in 4 standard colours

Coverage

- **Mineral TC 2:** 2 - 2.5 kg / sq m approx.
- **Mineral TC 4:** 4.5 - 5 kg / sq m approx.

Kitemark Classifications

- Compressive Strength: CSIII
- Capillary Water Absorption: W2

Sales & Technical Support:

Technical advice & product specifications are available from our Technical Support Centre on:

Tel: 028 2826 0766

Sales@K-Rend.co.uk

www.K-Rend.co.uk

